

SWAPLOADER®

U.S.A. LTD.

General Contractors - Landscapers - Lumber Yards - Municipals - Governmental - Rental Yards - Roofers - Waste Haulers

400 SERIES

33,000 - 40,000 LBS. LIFT CAPACITY



- **4 year warranty**
- **Sliding jib**
- **Slide through body locks**
- **Large beveled rear rollers**
- **Dual pivot rear section**
- **Dual lift cylinders**
- **Nylatron slide pads**
- **Low pressure hydraulics**
- **Integral dual counter balance valves**
- **Designed and built in the USA**

400 SERIES


NOTE:

THIS D
ILLUS

MODEL	SL-330	SL-400	SL-406	SL-412
Model Description	Dump Capacity (Incl. container)	33,000 lb	40,000 lb	40,000 lb
	Dump Angle	58°	58°	60°
	Lift Capacity (Incl. container)	33,000 lb	40,000 lb	40,000 lb
	Hoist Weight	Fixed 5,170 lb Adj 5,330 lb	Fixed 5,290 lb Adj 5,450 lb	Fixed 5,920 lb Adj 6,085 lb
General Dimensions (See Diagram)	Hook to Rear Roller (Dim. A)	167.5"	167.5"	209.75"
	Hook Height (Dim. B)	Fixed 61.75" Adj 61.75" - 53.88"	Fixed 61.75" Adj 61.75" - 53.88"	Fixed 61.75" Adj 61.75" - 53.88"
	Hoist Height (Dim. C)	11"	11"	11"
	Hoist CG (Dim. D)	88.8"	88.8"	114.0"
	Body Length (Dim. E) ②	14' to 18'	14' to 18'	18' to 22'
	Optimum Body Lengths	14' - 16'	14' - 16'	18' - 20'
	Body Longsill Width ③	40.5" or 41.75"	40.5" or 41.75"	40.5" or 41.75"
Hydraulic System	Hydraulic Pump Type (CID)	Gear (3.83)	Gear (3.83)	Gear (3.83)
	Flow ⑥	22.3 GPM @ 1,500 RPM	22.3 GPM @ 1,500 RPM	22.3 GPM @ 1,500 RPM
	Relief Pressure	3,600 PSI	3,600 PSI	3,600 PSI
	Hydraulic Resvr.	30 gal	30 gal	30 gal
Lift Cylinder	Type	All models incorporate twin, double acting cylinders with dual built-in counterbalance valves.		
	Quantity	2	2	2 ⑧
	Bore	Ø 5.5"	Ø 6"	Ø 6.5"
	Stroke	60"	60"	74"
Jib Cylinder ①	Type	All models incorporate a single, double acting cylinder with a single built-in counterbalance valve.		
	Quantity	1	1	1 ⑧
	Bore	Ø 4"	Ø 4"	Ø 4"
	Stroke	38"	38"	52"
Truck Specs (Recommended)	GVW Range	33,000 lb or greater	45,000 lb or greater	45,000 lb or greater
	Cab - Axle Dim. (Single Axle) ④	142" to 156"	N/A	N/A
	Cab - Trunion Dim. (Tandem Axle) ④	130" to 138"	130" to 138"	174" to 180"
	Truck Frame RBM	1,600,000 in lb	2,000,000 in lb	2,000,000 in lb
	Clear Frame Rail ⑤	191"	191"	232"
PTO Specs (Recommended)	Frame Height	up to 45"	up to 45"	up to 45"
	Pump Mount ⑦	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt
	Torque Required	200 ft-lbf	200 ft-lbf	200 ft-lbf

- 4 year warranty
- Sliding jib
- Slide through body locks
- Large beveled rear rollers
- Dual pivot rear section
- Rugged main frame
- Dual lift cylinders
- Nylatron slide pads
- Low pressure hydraulics
- Rigorous 4 year test cycle
- Integral Dual Counter Balance Valves
- Designed and Built in the USA

- 1 Jib Lock out valve to prevent jib operation in dump mode standard.
- 2 Hoist with longer bodies may not conform with I.C.C. bumper regulations or may not achieve maximum dump angle depending on truck chassis height. Contact your SwapLoader distributor for more information.
- 3 Maximum outside to outside longsill width.
- 4 Optimum CA/CT dimension will be influenced by type of loads carried and turning radius requirements.
- 5 Clear frame Dim given is the overall length of hoist plus 5" for cab clearance and rear light bar mounting. Additional frame length may be necessary for other accessories such as cab guard, tarper, exhaust system, etc.
- 6 Pump RPM and Flow are dependent on engine RPM and PTO ratio.
- 7 PTO/Pump rotation as determined by transmission.
- 8 Polished Nitrided Cylinder Rod.
- 9 Direct Mount Configuration Available.



SwapLoader USA, Ltd.
 1800 N.E. Broadway Ave.
 Des Moines, IA 50313
 Ph: 515-266-3042
 Fax: 515-313-4426
 Toll Free: 888-767-8000

Your authorized SwapLoader dealer

Ask about the wide range of available SwapLoader models

www.swaploader.com

SWL-053
 02/10 Rev 01/15