

# SWITCHLIFT TRAILER - PINTLE HITCH WITH SL145 MOUNTED HOIST

GVWR	14,000 lb
Axles	2 x 7,000 Dexter Torsion with Electric Brakes
Empty Trailer weight	5,300 lb
Overall Length (Empty)	19' 8"
Width	94"
Bed Length	10' - 15' Bodies
Coupler	Pintle (Convertible to Gooseneck with attachment)
Tires	235 / 80 / R16
Wheels	16"
Brakes	Electric
Fenders	Heavy Duty Aluminum
Jack	Hydraulic Remote Operation
Main Frame	Tubular
Gooseneck Frame	Tubular
Hydraulic Power Unit	Honda Engine IXG
Hook / Dumper Hyd Cylinder	Swaploader SL145 Fixed Jib Height
Control	Manual and Full Function Remote Control with Estart & Estop
Lights	All LED Markers / Directional / Work Lights
Camera	Optional
Stabilizer	Remote Operated Hydraulic Rear Stabilizer

## SWAPLOADER SL 145 HOIST

Dump Capacity (Inc. container)	14,000 lb
Dump Angle (Inc. container)	56°
Lift Capacity	14,000 lb
Hoist Weight	(Fixed Jib) 2,250 lb
Hook Height	35.63"
Body Length	10' to 15'
Hydraulic Pump Type (CID)	Gear Pump
Flow	8 GPM @ 1,000 RPM
Relief Pressure	2600 PSI
Hydraulic Resvr.	15 gal

## ADDITIONAL OPTIONS

Options	Roll Rite Pull Tarp
Options	Roll Rite Auto Tarp DC200
Options	Auxiliary Function Hydraulic Reel for Winch
Options	Wheel Tire & Suspension Upgrades Available

