

RE-INTRODUCING THE SWAPLOADER HOOK LIFT HOIST

SL-2418

DESIGNED FOR THE GOVERNMENTAL MARKET



24,000 LB LIFT/DUMP CAPACITY



POLISHED NITRIDED CYLINDER RODS



BOLT ON BODY LOCKS

FIXED 53 $\frac{7}{8}$ " HOOK HEIGHT

OPTIMUM BODY LENGTHS 10' – 12'



An EFCO Company

SWAPLOADER®

"Hooked on Quality"

U.S.A. LTD.

SPECIFICATIONS

MODEL		SL-2418
MODEL DESCRIPTION	DUMP CAPACITY (INCLUDING CONTAINER)	24,000 lb
	DUMP ANGLE	57°
	LIFT CAPACITY (INCLUDING CONTAINER)	24,000 lb
	HOIST WEIGHT	FIXED 3,040 lb ADJ. N/A
GENERAL DIMENSIONS (SEE DIAGRAM)	HOOK TO REAR ROLLER (DIM. A)	118.0"
	HOOK HEIGHT (DIM. B)	FIXED 53.88" ADJ. N/A
	HOIST HEIGHT (DIM. C)	9"
	HOIST CG (DIM. D)	63.8"
	BODY LENGTH (DIM. E)	10' - 13'
	OPTIMUM BODY LENGTHS	10' - 12'
	BODY LONGSILL WIDTH	41.63" / 40.5"
HYDRAULIC SYSTEMS	HYDRAULIC PUMP TYPE (CID)	Gear (4.46)
	FLOW @ PUMP RPM	17.4 GPM @ 1,000 RPM
	RELIEF PRESSURE	2,800 PSI
	HYDRAULIC RESVR.	25 gal
LIFT CYLINDER	QUANTITY	2
	BORE	Ø 5.5"
	STROKE	39"
JIB CYLINDER	QUANTITY	1
	BORE	Ø 4"
	STROKE	24"
TRUCK SPECS (RECOMMENDED)	GVW RANGE	25,000 lb - 35,000 lb
	CAB-AXLE DIM. (SINGLE AXLE)	84" to 96"
	CAB-TRUNION DIM. (TANDEM AXLE)	N/A
	CLEAR FRAME RAIL	134"
	FRAME HEIGHT	up to 43"
PTO SPECS (RECOMMENDED)	PUMP MOUNT	Direct Mount SAE B, 4 Bolt
	TORQUE REQUIRED	200 ft-lbf



ONE TRUCK UNLIMITED POSSIBILITIES

1800 NE Broadway Avenue, Des Moines, IA 50313 | web: swaploader.com | email: sales@swaploader.net | toll free: 888.767.8000 | phone: 515.266.3042

MADE IN USA

www.swaploader.com

 **YouTube**

SWL-957 SWAPLOADER 05/2020